



24



25



27



26



29

## Style 26, 29

### Grooved End Adaptor



### Style 26

#### Grooved-End / Threaded Reducing Elbow

	Nominal size	Pipe Outside Dia.	Reducing Elbow Style 26		Weight Kg.
			A	B	
inch	1½G x ½T	48.3 x ½"	1 13/16	1 17/32	0.33
mm	40 x 15		46.0	39.0	
inch	1½G x ¾T	48.3 x ¾"	1 59/64	1 5/8	0.40
mm	40 x 20		49.0	41.0	
inch	1½G x 1T	48.3 x 1"	2 3/32	1 21/32	0.47
mm	40 x 25		53.0	42.0	
inch	2G x ½T	60.3 x ½"	1 11/16	1 49/64	0.40
mm	50 x 15		43.0	45.0	
inch	2G x ¾T	60.3 x ¾"	1 49/64	1 55/64	0.47
mm	50 x 20		45.0	47.0	
inch	2G x 1T	60.3 x 1"	1 59/64	1 55/64	0.51
mm	50 x 25		49.0	47.0	

► Note: T=threaded (BSP) G=Grooved - end

### Style 29

#### Grooved / Threaded Elbow

	Nominal size	Pipe Outside Dia.	Dia.		Weight Kg.
			A	B	
inch	2Gx2T	2.375x2"	2 9/32	2 29/32	0.79
mm	50x50		58.0	74.0	

► Note: T=threaded (BSP) G=Grooved - end

Max working pressure: 300psi (20bar)

Thread type - BSP